



. ELECTRICAL CHARACTER:

- a. 100% OPEN&SHORT TESTING;
- b. WITHSTANDING VOLTAGE:DC 300V 0.01Sec;
- c. INSULATION RESISTANCE:10M Ohm(Min);
- d. CONDUCTIVE RESISTANCE:2 Ohm(Max).

10	LATCH	AQ-3-MS21008	STAINLESS STEEL	2	pcs
9	EXPANDO	AQ-3-MS76001	PET BALCK OD :10mm	A/R	mm
8	ACETATE TAPE	AQ-3-MS77001	w=25±5mm,BLACK	A/R	mm
7	MOLDING	AQ-3-GL10501	PA,BALCK	A/R	9
6	MOLDING	AQ-3-GL10501	PBT+20%GF,BALCK	A/R	9
5	MOLDING	AQ-3-GL10501	PE	A/R	9
4	PCBA	AQ-3-MS31027	SLIMSAS 8I PCB, PIN:30u Au, 85±10 ohm	1	PCS
3	HUOSING	AQ-3-MS64011	PA66+30%GF,BALCK	1	PCS
2	PCBA	AQ-3-MS31027	MCIO 8I PCB, 85±10 ohm	1	PCS
1	CABEL	AQ-3-MS40208	<30AWG*2C+2D>AL+MYLAR,OD:1.0*1.85MM,85±5 ohm	A/R	mm
NO.	PART NAME	PART NO.	SPEC DESCRIPTION	QT'Y	UNIT

